

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/03/2012

Revised On 01/03/2012

1 Identification of the substance and manufacturer

Trade name: HI TECH RED OXIDE PRIMER
Product code: 0000160807
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 Phone: 815-895-9101
 www.seymourpaint.com



Emergency telephone number: CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*

2 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	25.11%
74-98-6	propane	13.87%
106-97-8	n-butane	8.15%
108-88-3	Toluene	6.57%
64742-89-8	VM&P Naphtha	6.1%
1309-37-1	red iron oxide pigment	4.41%
64-17-5	ethyl alcohol	4.12%
1330-20-7	xylene (mix)	3.63%
123-86-4	n-butyl acetate	2.89%
64742-47-8	Mineral Spirits	1.93%
110-19-0	isobutyl acetate	1.68%
108-65-6	PM acetate	1.03%

3 Hazards identification

Hazard Information for people and the environment:

Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.
 Has narcotizing effect.

Risk phrases:

Extremely flammable.
 Irritating to eyes.
 Possible risk of harm to the unborn child
 Vapours may cause drowsiness and dizziness

Safety phrases:

Keep out of the reach of children.
 Keep away from sources of ignition - No smoking.
 Do not breathe gas/fumes/vapour/spray.
 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
 Wear suitable protective clothing and gloves.
 If swallowed, seek medical advice immediately and show this container or label.
 Use only in well-ventilated areas.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (0 - 4):

Health = 1
 Fire = 4
 Reactivity = 3

HMIS-ratings (0 - 4):

Health= 1
 Fire= 4
 Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Contact physician or poison control center.

5 Firefighting measures

Extinguishing agents: CO₂, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.
Special hazards: No further relevant information available.

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/03/2012

Revised On 01/03/2012

Trade name: HI TECH RED OXIDE PRIMER

Protective equipment: No special measures required.

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow product to reach sewage systems or ground water.

Methods and material for containment and cleaning up: Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL 2400 mg/m³, 1000 ppm
 REL 590 mg/m³, 250 ppm
 TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm
 Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm
 BEI

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
 REL 1800 mg/m³, 1000 ppm
 TLV Varies mg/m³, 1000 ppm

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
 TLV Varies mg/m³, 1000 ppm

108-88-3 Toluene

PEL Short-term value: C 300; 500* ppm
 Long-term value: 200 ppm
 *10-min peak per 8-hr shift
 REL Short-term value: 560 mg/m³, 150 ppm
 Long-term value: 375 mg/m³, 100 ppm
 TLV 75 mg/m³, 20 ppm
 BEI

64-17-5 ethyl alcohol

PEL 1900 mg/m³, 1000 ppm
 REL 1900 mg/m³, 1000 ppm
 TLV Short-term value: 1880 mg/m³, 1000 ppm

1330-20-7 xylene (mix)

PEL 435 mg/m³, 100 ppm
 REL Short-term value: 655 mg/m³, 150 ppm
 Long-term value: 435 mg/m³, 100 ppm
 TLV Short-term value: 651 mg/m³, 150 ppm
 Long-term value: 434 mg/m³, 100 ppm
 BEI

123-86-4 n-butyl acetate

PEL 710 mg/m³, 150 ppm
 REL Short-term value: 950 mg/m³, 200 ppm
 Long-term value: 710 mg/m³, 150 ppm
 TLV Short-term value: 950 mg/m³, 200 ppm
 Long-term value: 713 mg/m³, 150 ppm

110-19-0 isobutyl acetate

PEL 700 mg/m³, 150 ppm
 REL 700 mg/m³, 150 ppm
 TLV 713 mg/m³, 150 ppm

108-65-6 PM acetate

WEEL 50 ppm

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/03/2012

Revised On 01/03/2012

Trade name: HI TECH RED OXIDE PRIMER

(Contd. of page 3)

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4	ethyl benzene
108-10-1	methyl isobutyl ketone

California Proposition 65 chemicals known to cause developmental toxicity:

EPA: 108-88-3 Toluene
 A= Known human carcinogen B= Probable human carcinogen
 C= Possible human carcinogen
 D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).
 I: 'Data are inadequate for an assessment of human carcinogeni potential.'
 II: 'Inadequate information to assess carcinogenic potential.'

67-64-1	Acetone	I
108-88-3	Toluene	II
1330-20-7	xylene (mix)	I
110-19-0	isobutyl acetate	D

IARC: Group 2A: The ingredient is probably carcinogenic to humans.
 Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.
 Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	Toluene	3
1309-37-1	red iron oxide pigment	3
1330-20-7	xylene (mix)	3
14807-96-6	Talc (Mg3H2(SiO3)4)	3

ACGIH: A1-designates a confirmed human carcinogen.
 A2-designates a suspected human carcinogen.
 A3-designates an animal carcinogen.
 A4-designates "not classifiable as a human carcinogen".

67-64-1	Acetone	A4
108-88-3	Toluene	A4
1309-37-1	red iron oxide pigment	A4
64-17-5	ethyl alcohol	A3
1330-20-7	xylene (mix)	A4
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
110-19-0	isobutyl acetate	A4

NIOSH: The following substances are regulated in the United States with reference to occupational exposure limits:

The following substances are regulated in the United States with reference to occupational exposure limits:

16 Other information

This product was manufactured in the U.S.A.
 The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms:

GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 PP: Severe Marine Pollutant
 P: Marine Pollutant
 HMIS: Hazardous Materials Identification System (USA)
 ISO: International Organization for Standardization
 EPA: Environmental Protection Agency
 IARC: International Agency for the Research of Cancer
 NIOSH: National Institute for Occupational Safety and Health
 TSCA: Toxic Substances Control Act
 CPSC: Consumer Product Safety Commission