

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2012

Revised On 01/05/2012

## 1 Identification of the substance and manufacturer

**Trade name:** QUIET SEAL I UNDERCOATING  
**Product code:** 0000200006  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178  
 Phone: 815-895-9101  
 www.seymourpaint.com



**Emergency telephone number:** CHEMTEL 1-800-255-3924, 813-248-0585 \*if located outside the U.S.\*

## 2 Composition/information on ingredients

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

8052-42-4	Asphalt	19.62%
74-98-6	propane	12.6%
1332-58-7	Aluminum Silicate	7.66%
106-97-8	n-butane	7.4%
64742-47-8	Mineral Spirits	3.37%
108-88-3	Toluene	3.36%
67-56-1	methanol	1.92%

## 3 Hazards identification

### Hazard Information for people and the environment:

Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.  
 Has narcotizing effect.

### Risk phrases:

Extremely flammable.

### Safety phrases:

Keep out of the reach of children.  
 Keep away from sources of ignition - No smoking.  
 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point  
 If swallowed, seek medical advice immediately and show this container or label.  
 Use only in well-ventilated areas.

### Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

### NFPA ratings (0 - 4):

Health- 1  
 Fire- 3  
 Reactivity- 3

### HMIS-ratings (0 - 4):

Health- 1  
 Flammability- 3  
 Physical Hazard- 3

## 4 First aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.  
**After swallowing:** Contact physician or poison control center.

## 5 Firefighting measures

**Extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.  
**Special hazards:** No further relevant information available.  
**Protective equipment:** No special measures required.

## 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.  
**Environmental precautions:** Do not allow product to reach sewage systems or ground water.

(Contd. on page 2)  
 —USA—

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2012

Revised On 01/05/2012

Trade name: QUIET SEAL I UNDERCOATING

(Contd. of page 1)

### Methods and material for containment and cleaning up:

Ensure adequate ventilation.

## 7 Handling and storage

**Fire/explosion protection:** Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

**Storage requirements:** Observe pressurized container storage regulations. Consult with your local authorities.

## 8 Exposure controls/personal protection

### Components with limit values that require monitoring at the workplace:

#### 8052-42-4 Asphalt

REL Short-term value: C 5\* mg/m<sup>3</sup>  
\*15-min; See Pocket Guide App. A  
TLV 0.5\* mg/m<sup>3</sup>  
\*inh. fraction; as benzene-soluble aerosol; BEIp

#### 74-98-6 propane

PEL 1800 mg/m<sup>3</sup>, 1000 ppm  
REL 1800 mg/m<sup>3</sup>, 1000 ppm  
TLV Varies mg/m<sup>3</sup>, 1000 ppm

#### 1332-58-7 Aluminum Silicate

PEL 15\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fraction  
REL 10\* 5\*\* mg/m<sup>3</sup>  
\*total dust \*\*respirable fraction  
TLV 2\* mg/m<sup>3</sup>  
E; as respirable fraction

#### 106-97-8 n-butane

REL 1900 mg/m<sup>3</sup>, 800 ppm  
TLV Varies mg/m<sup>3</sup>, 1000 ppm

#### 108-88-3 Toluene

PEL Short-term value: C 300; 500\* ppm  
Long-term value: 200 ppm  
\*10-min peak per 8-hr shift  
REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
TLV 75 mg/m<sup>3</sup>, 20 ppm  
BEI

#### 67-56-1 methanol

PEL 260 mg/m<sup>3</sup>, 200 ppm  
REL Short-term value: 325 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 260 mg/m<sup>3</sup>, 200 ppm  
Skin  
TLV Short-term value: 328 mg/m<sup>3</sup>, 250 ppm  
Long-term value: 262 mg/m<sup>3</sup>, 200 ppm  
Skin; BEI

**Hygienic protection:** Wash hands after use.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

**Eye protection:** Tightly sealed goggles

## 9 Physical and chemical properties

**Odor:** Aromatic

**pH-value:** Not determined.

**Boiling point:** -44°C (-47 °F)

**Flash point:** -19°C (-2 °F)

**Flammability (solid, gaseous):** Not applicable.

**Auto igniting:** Product is not self-igniting.

**Danger of explosion:** Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.  
In use, may form flammable/explosive vapour-air mixture.

**Lower Explosion Limit:** 1.7 Vol %

**Upper Explosion Limit:** 10.9 Vol %

**Vapor Pressure:** 40 PSI, 2750 hPa

(Contd. on page 3)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2012

Revised On 01/05/2012

**Trade name: QUIET SEAL I UNDERCOATING**

(Contd. of page 2)

**Specific Gravity:** Between 0.77 and 0.85 (Water equals 1.00)  
**VOC content:** 365.5 g/l / 3.05 lb/gl  
**VOC content (less exempt solvents):** 28.6 %  
**Water:** 31.0 %  
**MIR Value:** 0.30  
**Solids content:** 40.4 %  
**Other information** No further relevant information available.

## 10 Stability and reactivity

**Conditions to avoid:** Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.  
**Hazardous decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

**Skin effects:** No irritant effect.  
**Eye effects:** No irritating effect.  
**Sensitization:** No sensitizing effects known.

## 12 Ecological information

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

## 13 Disposal considerations

**DISPOSAL METHOD:** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

**DOT** N/A  
**DOT** AEROSOLS, flammable  
**DOT Class** 2.1  


---

  
**ADR Class** 2 5F Gases  
**Label** 2.1  
**Environmental hazards:**  
**Marine pollutant:** No  
**EMS Number:** F-D,S-U  
**Packaging Group:** --

## 15 Regulatory information

### SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

### SARA Section 313 (Specific toxic chemical listings):

108-88-3	Toluene
67-56-1	methanol

**TSCA:** All ingredients are listed.**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

### California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

### California Proposition 65 chemicals known to cause developmental toxicity:

108-88-3 Toluene

### EPA:

108-88-3	Toluene	II
----------	---------	----

### IARC:

8052-42-4	Asphalt	3
108-88-3	Toluene	3

### ACGIH:

8052-42-4	Asphalt	A4
1332-58-7	Aluminum Silicate	A4

(Contd. on page 4)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/05/2012

Revised On 01/05/2012

<b>Trade name: QUIET SEAL I UNDERCOATING</b>
--

(Contd. of page 3)

108-88-3	Toluene
----------	---------

A4
----

**NIOSH:**

8052-42-4	Asphalt
-----------	---------

### 16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Contact:** Regulatory Affairs

**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 ISO: International Organization for Standardization  
 EPA: Environmental Protection Agency  
 IARC: International Agency for the Research of Cancer  
 NIOSH: National Institute for Occupational Safety and Health  
 TSCA: Toxic Substances Control Act  
 CPSC: Consumer Product Safety Commission

USA