

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

1 Identification of substance

Trade name: MRO GLOSS BLACK

Product code: 0006201415

Manufacturer/Supplier: SEYMOUR OF SYCAMORE
917 Crosby Avenue
Sycamore, IL 60178
(815)-895-9101, www.seymourpaint.com

Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*



2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	22.56%
74-98-6	propane	15.75%
106-97-8	n-butane	9.25%
7727-43-7	barium sulphate, natural	8.51%
2807-30-9	Glycol Ether EP	5.45%
108-10-1	methyl isobutyl ketone	5.16%
107-87-9	Methyl Propyl Ketone	3.33%
1330-20-7	xylene (mix)	2.69%
108-65-6	PM acetate	1.83%
110-19-0	isobutyl acetate	1.41%

3 Hazards identification

Hazard description:



Irritant
Extremely flammable

Physical dangers:

Extremely flammable.
Irritating to eyes.
Vapours may cause drowsiness and dizziness
Keep out of the reach of children.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (scale 0 - 4):

Health = 1
Fire = 4
Reactivity = 3

HMIS-ratings (scale 0 - 4):

Health= 1
Fire= 4
Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Contact physician or poison control center.

5 Fire fighting measures

Extinguishing agents: CO₂, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

Protective equipment: No special measures required.

6 Accidental release measures

Personal safety precautions: Wear protective equipment. Keep unprotected persons away.

Environmental safety precautions: Do not allow product to reach sewage systems or ground water.

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

Trade name: MRO GLOSS BLACK

(Contd. of page 1)

Measures for cleaning/collecting: Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

8 Exposure controls and personal protection:

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm Long-term value: 1188 mg/m ³ , 500 ppm BEI

74-98-6 propane

PEL	1800 mg/m ³ , 1000 ppm
REL	1800 mg/m ³ , 1000 ppm
TLV	Varies mg/m ³ , 1000 ppm

106-97-8 n-butane

REL	1900 mg/m ³ , 800 ppm
TLV	Varies mg/m ³ , 1000 ppm

7727-43-7 barium sulphate, natural

PEL	15* 5** mg/m ³ *total dust **respirable fraction
REL	10* 5** mg/m ³ *total dust **respirable fraction
TLV	10 mg/m ³ E

108-10-1 methyl isobutyl ketone

PEL	410 mg/m ³ , 100 ppm
REL	Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm
TLV	Short-term value: 307 mg/m ³ , 75 ppm Long-term value: (205) NIC-123 mg/m ³ , (50) NIC-30 ppm BEI;NIC-A3

107-87-9 Methyl Propyl Ketone

PEL	700 mg/m ³ , 200 ppm
REL	530 mg/m ³ , 150 ppm
TLV	Short-term value: 529 mg/m ³ , 150 ppm

1330-20-7 xylene (mix)

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

108-65-6 PM acetate

WEEL	50 ppm
------	--------

110-19-0 isobutyl acetate

PEL	700 mg/m ³ , 150 ppm
REL	700 mg/m ³ , 150 ppm
TLV	713 mg/m ³ , 150 ppm

Protective hygienic measures:

Breathing equipment: Keep away from foodstuffs and animal feed. Wash hands after use. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. Please consult an authority on chemical hygiene monitoring if you suspect overexposure conditions exist and need a specific recommendation on proper ventilation techniques and personal protection.

Protection of hands: Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

Trade name: MRO GLOSS BLACK

Eye protection: Tightly sealed goggles

(Contd. of page 2)

9 Physical and chemical properties:

General Information:

Odor:	Aromatic
Boiling point/Boiling range:	-44°C
Flash point:	-19°C
Ignition temperature:	230°C
Auto igniting:	Product is not self-igniting.
Danger of explosion:	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor Pressure:	40 PSI, 2750 hPa
Density at 20°C:	0.82201 g/cm ³
Specific Gravity:	Between 0.77 and 0.85 (Water equals 1.00)
VOC content:	495.5 g/l / 4.14 lb/gl
VOC content (less exempt solvents):	46.2 %
MIR value:	46.2 %
MIR Value:	1.11
Solids content:	30.9 %

10 Stability and reactivity:

Conditions to be avoided: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
Possibility of Hazardous Reactions: No dangerous reactions known.

11 Toxicological information:

Primary effect on the skin: No irritant effect.
Primary effect on the eye: Irritating effect.
Sensitization: No sensitizing effects known.
Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations:

12 Ecological information

Other information: This product does not contain any chloroflourocarbons (CFC's),chlorinated solvents, lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether (PDBE). No specific ecological data is available for this product.
Acquatic toxicity: Hazardous for water, do not empty into drains.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information:

Hazard class:	2.1
Identification number:	N/A
Label:	2.1+8
ADR/RID class:	2 5FC Gases
UN-Number:	1950
IMDG Class:	2.1
Packaging group:	II
EMS Number:	F-D,S-U

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

Trade name: MRO GLOSS BLACK

(Contd. of page 3)

Marine pollutant: No
ICAO/IATA Class: 2.1
Propper shipping name: Aerosols, Flammable
 Consumer Commodity ORM-D

15 Regulations

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-10-1 methyl isobutyl ketone

1330-20-7 xylene (mix)

TSCA (Toxic Substances

Control Act): All ingredients are listed.

PROPOSITION 65 Chemicals known to cause cancer:

1333-86-4 Carbon black

100-41-4 ethyl benzene

EPA: A= Known human carcinogen B= Probable human carcinogen
 C= Possible human carcinogen
 D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

67-64-1	Acetone	I
108-10-1	methyl isobutyl ketone	I
1330-20-7	xylene (mix)	I
110-19-0	isobutyl acetate	D

IARC: Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

1330-20-7	xylene (mix)	3
-----------	--------------	---

ACGIH TLVs: A1-designates a confirmed human carcinogen.
 A2-designates a suspected human carcinogen.
 A3-designates an animal carcinogen.
 A4-designates "not classifiable as a human carcinogen".

67-64-1	Acetone	A4
1330-20-7	xylene (mix)	A4
110-19-0	isobutyl acetate	A4

NIOSH:

1333-86-4 Carbon black

Risk phrases: Extremely flammable.
 Irritating to eyes.
 Vapours may cause drowsiness and dizziness

Safety phrases: Keep out of the reach of children.
 Keep in a cool place.
 Keep container in a well-ventilated place.
 Keep away from food, drink and animal feedingstuffs.
 Keep away from sources of ignition - No smoking.
 Do not breathe gas/fumes/vapour/spray.
 Avoid contact with eyes.
 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point
 If swallowed, seek medical advice immediately and show this container or label.
 Use only in well-ventilated areas.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 5)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/14/2008

Reviewed on 11/14/2008

Trade name: MRO GLOSS BLACK

(Contd. of page 4)

IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
VOC: Volatile Organic Compounds (USA, EU)

USA