



FILL ONE UNIVERSAL SOLVENT BLEND

#16-2395, #C16-2395, #16-3395, #C16-3395, #16-4395, #C16-4395

A specialized blend of solvents and propellant which can be used to aerosolize most enamel, lacquer, vinyl, and acrylic paints. The unique cap functions as the paint reservoir during the filling process. There is no prep or cleanup work involved. To be used exclusively with the Z-2500, Z-2501 and Z-2507 Fill One Machines.

Suggested Uses:

Aerosolize custom matched colors
Automotive touch up
Maintenance and industrial
OEM applications

Benefits:

An extremely convenient way to create aerosol products in small quantities.
One SKU reduces number and quantity of aerosol blank cans to be inventoried
Ordering is simple and convenient
Easier to generate orders for Seymour products, or to reach prepaid freight minimums.

Packaging:

UPC Code	
Cans per case	12
Shipping weight per case	13.6 lbs.
Container	16 fluid ounce can
Label weight	8 ounces
Shipping Classification	ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Extremely Flammable"
Flash point	-19C
Specific Gravity	0.69
VOC content	~34%
MIR value	~0.74
HAPs content	0%
Storage Temperature	40-100F
Application Temperature	50-90F
Shelf life Unfilled:	Guaranteed for 2 years

Filled cans should be used as soon as possible.

Dry Time*:

Not Applicable

*At 72° F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Not Applicable

*as measured on a 60° gloss meter

Additional Information:

NOT FOR USE WITH WATER REDUCIBLE PAINT. While Seymour of Sycamore has tested paints from many different manufacturers, compatibility with the **Solvent Blend** aerosols can not be guaranteed. Additional label information and/or warnings may be required if the injected product's safety information varies from that of the **Solvent Blend**. Filling aerosol cans is a manufacturing process, and the manufacturer is ultimately responsible for complying with hazardous labeling standards.