



Hi Tech H₂O Industrial Enamel

A superior, non-flammable aerosol coating formulated for maintenance operations where maximum performance is required. This paint offers single coat hiding and corrosion resistance with minimal odor.

Suggested Uses:

Excellent wood and metal:
Blowers
Benches
Machinery
Racks
Metal doors
Bins
Piping

Benefits:

Includes OSHA safety colors
Single coat hiding
Resists abrasion and heat
Low odor

Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	Not flammable
Flash point	-42F (propellant only)
Specific Gravity	0.85
Solids Content	~13%
VOC content	~47%, cannot exceed 65%
MIR value	~0.54, cannot exceed 1.40
HAPs content	0%
Storage Temperature	40-90F
Application Temperature	50-100F
Durability	Excellent
Abrasion Resistance	Good
Heat Resistance	300° F
Gasoline Resistance	Yes
Resin System	Water Reducible Alkyd
Shelf life	Guaranteed for 1 year
Food contact rating	Not acceptable

Dry Time*:

To touch	60 minutes
Tack free	120 minutes
Recoat time	before 1 hour or after 48 hours

*At 72° F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: High Gloss, >85

*as measured on a 60° gloss meter

Available Colors:

Part #	Description	UPC Code
16-5413	Gloss White	043281005548
16-5415	Gloss Black	043281005555
16-5417	Dark Machinery Gray	043281005562
16-5419	Safety Yellow	043281005579
16-5423	Safety Red	043281005586
16-5427	Safety Blue	043281005593
16-5451	Safety Orange	043281005609
16-5452	Safety Green	043281005616