



MRO Plus High Solids Enamels

A superior, lead-free industrial coating formulated for maintenance operations where maximum performance is required. This paint does not run or sag, and offers the highest solid content (40%) of any aerosol paint on the market for maximum coverage. For best results, use our MRO Red Iron Oxide Primer (620-1407) or Light Gray Primer (620-1431).

Suggested Uses:

Wood and metal
Home
Automotive
Industrial
Marine
Construction

Benefits:

Protects against rust, weather, oil, gasoline and most corrosive chemicals
Includes OSHA safety colors
Single coat hiding
Resists abrasion and heat
Withstands high humidity

Packaging:

| | |
|--------------------------|-----------------------------------|
| Cans per case | 6 |
| Shipping weight per case | 9 lbs. |
| Container | 20 fluid ounce can |
| Label weight | 16 ounces (454 grams) |
| Shipping Classification | Consumer Commodity ORM-D, UN 1950 |
| Hazard Class | 2.1 |
| Flammability | "Extremely Flammable" |

Properties:

| | |
|-------------------------|--|
| Flash point | -4 ⁰ F |
| Specific Gravity | 0.82 |
| Solids Content | 40% |
| VOC content | Glosses: ~58%, cannot exceed 65% Flats: ~56%, cannot exceed 60% |
| MIR value | Glosses: ~1.10, cannot exceed 1.40 Flats: ~1.12, cannot exceed 1.20 |
| HAPs content | ~13% |
| Storage Temperature | 40-100F |
| Application Temperature | 50-90F |
| Durability | Excellent |
| Abrasion Resistance | Good |
| Gasoline Resistance | No |
| Heat Resistance | 300 ⁰ F |
| Resin System | Chain Stopped alkyd |
| Shelf life | Guaranteed for 2 years |
| Food contact rating | Category 21: Acceptable for incidental food contact |

Dry Time*:

| | |
|-----------|---------------------------------|
| To touch | 10 minutes |
| Tack free | 30 minutes |
| To recoat | Before 1 hour or after 48 hours |

*At 72⁰ F, 50% humidity, 1.5 mil thickness

****Curing/Recoat time is extended with multiple coats and excessively thick coats****

| | |
|----------------|-----------------|
| Gloss*: | High Gloss, >80 |
| | Flat, <15 |

*as measured on a 60⁰ gloss meter

Available Colors:

| Part # | Description | UPC Code | Part # | Description | UPC Code |
|----------|----------------------|--------------|----------|---------------|--------------|
| 620-2412 | Flat White | 043281004152 | 620-2419 | Safety Yellow | 043281004237 |
| 620-2413 | Gloss White | 043281004183 | 620-2423 | Safety Red | 043281004244 |
| 620-2415 | Gloss Black | 043281004190 | 620-2427 | Safety Blue | 043281004251 |
| 620-2416 | ANSI 61 Gray | 043281004206 | 620-2433 | Flat Black | 043281004992 |
| 620-2417 | Dark Machinery Gray | 043281004213 | 620-2451 | Safety Orange | 043281005001 |
| 620-2418 | Light Machinery Gray | 043281004220 | 620-2452 | Safety Green | 043281005012 |