



## SEAL-IT Multi Purpose Sealant

A next generation multi-purpose sealant that adheres to any surface, with the flexibility and durability to hold up under the most demanding conditions. Due to its thermoplastic elastomer base, this sealant will not crack in cold temperatures, is impervious to water, and protects substrates in corrosive environmental conditions.

### Suggested Uses:

Skylights  
Flashings  
Air vents  
Driveway and sidewalk cracks  
Gutters  
Shingles

### Benefits:

Does not lose flexibility  
Protects against UV light  
Resists temperature extremes  
Impervious to water  
Abrasion resistant

### Packaging:

Cans per case	12
Shipping weight per case	19 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	Consumer Commodity, ORM-D, UN 1950
Hazard Class	2.1

### Properties:

Flammability	"Extremely Flammable"
Flash point	-4° F
Specific Gravity	.82
Solids Content	~31%
VOC content	~59%, cannot exceed 60%
MIR value	~1.15, cannot exceed 1.20
HAPs content	~4%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Excellent
Abrasion Resistance	Very Good
Heat Resistance	250° F
Resin System	Thermoplastic Elastomer
Shelf life	Guaranteed for 2 years
Food contact rating	No

### Dry Time\*:

Tack free	10 minutes
To recoat	10 minutes

\*At 72° F, 50% humidity,  
1.5 mil thickness

\*\*Curing/Recoat time is extended with multiple coats and excessively thick coats\*\*

**Gloss\*:** Flat, <15

\*as measured on a 60° gloss meter

### Available Colors:

Part #	Description	UPC Code
#20-147	White	043281005029
#20-148	Black	043281005036
#20-149	Clear	043281005043
#20-150	Silver	043281005074

### Additional Information:

This product leaves a slightly bubbly film. When covering a broad area it is recommended that two coats be applied to ensure a non-porous final coating. Allow first coat to dry to touch (about 8-10 minutes) before applying the second and final coat.