



PIT CREW TINTED IGNITION SEALER #16-329 Red

A fortified polymer coating to protect ignition systems from moisture, current leakage, acid and corrosion. Wiring should be clean and dry prior to spraying.

Suggested Uses:

All types of ignition and electrical systems.
Electrical equipment
Motor end windings, communicator ends, field coatings and armatures.

Benefits:

Excellent dielectric strength.
Orange tint for uniform coverage.
Waterproofs and insulates.
Reduces electrical system maintenance

Packaging:

UPC Code	
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Extremely Flammable"
Flash point	-4F
Specific Gravity	0.80
Solids Content	~14%
VOC content	~55%, cannot exceed 65%
MIR value	~1.34, cannot exceed 1.40
HAPs content	~22%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Excellent
Abrasion Resistance	Excellent
Gas Resistance	No
Heat Resistance	250° F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch 10 minutes

*At 72° F, 50% humidity,
1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: High Gloss, >85

*as measured on a 60° gloss meter

Available Colors: