

## Safety Data Sheet

Printing date 01/10/2020

Revised On 01/02/2020

## 1 Identification of the substance and manufacturer

**Trade name:** COLD GALVANIZE (MRO) GALLONS  
**Product code:** 0000011445  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178 USA  
 phone: 815-895-9101  
 www.seymourpaint.com

**Emergency telephone number:** 1-800-255-3924

Seymour of Sycamore  
 3041 Dougall Avenue, Suite 503  
 Windsor, ONT N9E 1S3 CANADA  
 phone: 800-435-4482  
 www.seymourpaint.com

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flam. Liq. 2 H225 Highly flammable liquid and vapor.  
 Eye Irrit. 2A H319 Causes serious eye irritation.  
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

## GHS Hazard pictograms



GHS02 GHS07 GHS08

## Signal word

Danger

## Hazard statements

Highly flammable liquid and vapor.  
 Causes serious eye irritation.

## Precautionary statements

May cause damage to organs through prolonged or repeated exposure.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash hands thoroughly after handling.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

540-88-5	tert-butyl acetate	5-10%
64742-89-8	VM&P Naphtha	5-10%
64742-47-8	Mineral Spirits	1-5%

## 4 First-aid measures

**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
**After swallowing:** Rinse out mouth and then drink plenty of water.  
 Rinse mouth with water. Do not induce vomiting.

**Most important symptoms and effects:** No further relevant information available.  
**Indication of any immediate medical attention needed:** No further relevant information available.

## 5 Fire-fighting measures

**Special hazards:** No further relevant information available.  
**Protective equipment for firefighters:** No special measures required.

## 6 Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** Wear protective equipment. Keep unprotected persons away.  
**Methods and material for containment and cleaning up:** Ensure adequate ventilation.

(Contd. on page 2)

## Safety Data Sheet

Printing date 01/10/2020

Revised On 01/02/2020

Trade name: COLD GALVANIZE (MRO) GALLONS

(Contd. of page 1)

 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
**7 Handling and storage****Precautions for safe handling  
Storage requirements:**

Use only in well ventilated areas.  
Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.  
Store locked up.

**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****540-88-5 tert-butyl acetate**

PEL (USA)	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
REL (USA)	Long-term value: 950 mg/m <sup>3</sup> , 200 ppm
TLV (USA)	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

**Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.  
Immediately remove all soiled and contaminated clothing.  
Wash hands after use.  
Avoid contact with the eyes and skin.  
Do not eat or drink while working.

**Breathing equipment:**

Not required.

**Hand protection:**

Nitrile gloves.

**Eye protection:**

The glove material must be impermeable and resistant to the substance.  
Tightly sealed goggles

**9 Physical and chemical properties**

<b>Appearance:</b>	Liquid.
<b>Odor threshold:</b>	Not determined.
<b>pH-value:</b>	Not determined.
<b>Melting point/Melting range</b>	Undetermined.
<b>Boiling point:</b>	85 °C (185 °F)
<b>Flash point:</b>	-19 °C (-66.2 °F)
<b>Flammability (solid, gas):</b>	Highly flammable.
<b>Decomposition temperature:</b>	Not determined.
<b>Auto igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
<b>Lower Explosion Limit:</b>	Not determined.
<b>Upper Explosion Limit:</b>	Not determined.
<b>Vapor pressure:</b>	Not determined.
<b>Vapor density</b>	Not determined.
<b>Evaporation rate</b>	Not determined.
<b>Partition coefficient: n-octanol/water:</b>	Not determined.
<b>Solubility:</b>	Not determined.
<b>Viscosity:</b>	Not determined.
<b>VOC content (less exempt solvents):</b>	10.2 %

**10 Stability and reactivity**

<b>Conditions to avoid:</b>	No decomposition if used according to specifications.
<b>Possibility of hazardous reactions:</b>	No dangerous reactions known.
<b>Incompatible materials:</b>	No further relevant information available.
<b>Hazardous decomposition:</b>	No dangerous decomposition products known.

**11 Toxicological information**

<b>Information on toxicological effects:</b>	No data available.
<b>Skin effects:</b>	No irritant effect.
<b>Eye effects:</b>	Irritating effect.
<b>Sensitization:</b>	No sensitizing effects known.

**12 Ecological information**

<b>Aquatic toxicity:</b>	Hazardous for water, do not empty into drains.
<b>Persistence and degradability:</b>	The product is degradable after prolonged exposure to natural weathering processes.
<b>Other information:</b>	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
<b>Bioaccumulative potential:</b>	No further relevant information available.

(Contd. on page 3)

## Safety Data Sheet

Printing date 01/10/2020

Revised On 01/02/2020

Trade name: COLD GALVANIZE (MRO) GALLONS

**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

(Contd. of page 2)

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

**14 Transport information**

**ADR** 1263 Paint  
**Transport hazard class(es):**  
**Class** 3 Flammable liquids  
**Marine pollutant:** No  
 Symbol (fish and tree)  
**Special precautions for user:** Warning: Flammable liquids  
**EMS Number:** F-E, S-E  
**Stowage Category** B  
**Packaging Group:** II  
**UN "Model Regulation":** UN 1263 PAINT

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

7440-66-6 zinc powder

1314-13-2 zinc oxide

**Toxic Substances Control Act****(TSCA):** All hazardous ingredients are found on the inventory list of substances.**Canadian Domestic Substances List****(DSL):** All ingredients are listed or exempted.**Consumer Product Safety****Commission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

None of the ingredients in this product are listed.

**Prop 65 chemicals known to cause birth defects or reproductive harm:**

None of the ingredients is listed.

**EPA:**

7440-66-6 zinc powder

D, I, II

1314-13-2 zinc oxide

D, I, II

**16 Other information****Contact:** Regulatory Affairs