



## ALUMINUM BASE COAT #16-532

This is the Aluminum Base Coat specifically recommended for use under Seymour's Reflective Coatings. This base coat is a quick drying lacquer. The reflective top coat can be applied immediately after the base coat is dry, in approximately two minutes.

### Suggested Uses:

The base coat for use under Seymour Reflective Coatings

### Packaging:

UPC Code	043281001373
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

### Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	13%
MIR value	1.18, cannot exceed 1.25
HAPs content	33%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Fair
Abrasion Resistance	Poor ( <b>product will burnish</b> )
Heat Resistance	250F
Resin System	Lacquer
Shelf life	Guaranteed for 2 years

### Dry Time\*:

To touch	5 minutes
To recoat	15 minutes

\*At 72F, 50% humidity,  
1.5 mil thickness

\*\*Curing/Recoat time is extended with  
multiple coats and excessively thick coats\*\*

**Gloss\*:** Flat, <15

\*as measured on a 60 degree gloss meter

12-11-2019