



SHINY GALV #16-841

A shiny zinc enhanced zinc coating that prevents rust and provides excellent outdoor protection. This is the product of choice for the cosmetic restoration of galvanized metal, chain link fences, and guard rails. *Does not* meet specifications calling for 65% zinc in the can or greater than 90% zinc in the dried paint film. Fast dry, prevents rust, and has excellent outdoor durability.

Suggested Uses:

All vehicle bodies
Agricultural, mining and construction equipment
Piping, storage tanks
Bridges
Ships and marine equipment

Packaging:

UPC Code	043281007221
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.78
Solids Content	23%
Zinc in dried paint film	4%
MIR value	1.16, cannot exceed 1.25
HAPs content	32%
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250F
Resin System	Epoxy
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch	10 minutes
To recoat	anytime

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

12-19-2019