



OE SHINY GALV

#16-842

A shiny galvanized coating that protects and matches new galvanized metal. Resists oxidation and eliminates the need for an aluminum topcoat. Excellent for restoration of chain link fences and guardrails. The dried paint film contains a minimum of 65% zinc. It is considered a sacrificial coating, and meets ASTM A780 performance specifications.

Suggested Uses:

All vehicle bodies
Agricultural, mining and construction equipment
Piping, storage tanks
Bridges
Ships and marine equipment

Packaging:

UPC Code	043281006934
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	13 ounces (369 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.87
Solids Content	19%
% Zinc in dried paint film	65.5%
MIR value	0.73, cannot exceed 1.25
HAPs content	15%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Very Good
Abrasion Resistance	Good
Heat Resistance	250F
Resin System	Acrylic
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
To topcoat	20 minutes

*At 72F, 50% humidity,
1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: Flat, <15*

*as measured on a 60 degree gloss meter

12-19-2019