

Safety Data Sheet

Printing date 01/10/2020

Revised On 01/06/2020

1 Identification of the substance and manufacturer

Trade name: ATHLETIC FIELD RED
Product code: 0000200643
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com

Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irrit. 2 H315 Causes skin irritation.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Danger

Hazard statements

Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash hands thoroughly after handling.
 If skin irritation occurs: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.
 Store in a well-ventilated place.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|------------|-------------------|---------|
| 1317-65-3 | Calcium Carbonate | 10-15% |
| 74-98-6 | propane | 10-15% |
| 64742-89-8 | VM&P Naphtha | 5-10% |
| 106-97-8 | n-butane | 5-10% |
| 142-82-5 | heptane | ≥5-<10% |
| 64742-47-8 | Mineral Spirits | 5-10% |
| 1330-20-7 | xylene (mix) | 1-5% |

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects: Dizziness
Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.
Protective equipment for firefighters: A respiratory protective device may be necessary.

(Contd. on page 2)

Safety Data Sheet

Printing date 01/10/2020

Revised On 01/06/2020

Trade name: ATHLETIC FIELD RED

(Contd. of page 1)

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage**Precautions for safe handling**

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****74-98-6 propane**PEL (USA) Long-term value: 1800 mg/m³, 1000 ppmREL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F in TLVs&BEIs book; D, EX

106-97-8 n-butaneREL (USA) Long-term value: 1900 mg/m³, 800 ppmTLV (USA) Short-term value: 2370 mg/m³, 1000 ppm (EX)**142-82-5 heptane**PEL (USA) Long-term value: 2000 mg/m³, 500 ppmREL (USA) Long-term value: 350 mg/m³, 85 ppm
Ceiling limit value: 1800* mg/m³, 440* ppm
*15-minTLV (USA) Short-term value: 2050 mg/m³, 500 ppm
Long-term value: 1640 mg/m³, 400 ppm**1330-20-7 xylene (mix)**PEL (USA) Long-term value: 435 mg/m³, 100 ppmREL (USA) Short-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmTLV (USA) Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI**Ingredients with biological limit values:****1330-20-7 xylene (mix)**

BEI (USA) 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

Hygienic protection:

Wash hands after use.

Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.

If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties**Appearance:**

Aerosol.

Odor:

Aromatic

Odor threshold:

Not determined.

pH-value:

Not determined.

Melting point/Melting range

Undetermined.

Boiling point:

-44 °C (-111.2 °F)

Flash point:

-19 °C (-66.2 °F)

Flammability (solid, gas):

Extremely flammable.

Decomposition temperature:

Not determined.

Auto igniting:

Product is not self-igniting.

Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit:

1.7 Vol %

(Contd. on page 3)

Safety Data Sheet

Printing date 01/10/2020

Revised On 01/06/2020

Trade name: ATHLETIC FIELD RED

(Contd. of page 2)

| | |
|--|---|
| Upper Explosion Limit: | 10.9 Vol % |
| Vapor pressure: | Not determined. |
| Relative Density: | Between 0.77 and 0.85 (Water equals 1.00) |
| Vapor density: | Not determined. |
| Evaporation rate: | Not applicable. |
| Partition coefficient: n-octonal/water: | Not determined. |
| Solubility: | Not determined. |
| Viscosity: | Not determined. |
| VOC content (less exempt solvents): | 45.5 % |
| Water: | 30.0 % |

10 Stability and reactivity

| | |
|--|--|
| Reactivity: | Stable at normal temperatures. |
| Conditions to avoid: | Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures. |
| Chemical stability: | Not fully evaluated. |
| Possibility of hazardous reactions: | No dangerous reactions known. |
| Incompatible materials: | No further relevant information available. |
| Hazardous decomposition: | No dangerous decomposition products known. |

11 Toxicological information**LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

1330-20-7 xylene (mix)

Oral LD50 8,700 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rbt)

Inhalative LC50/4 h 6,350 mg/l (rat)

| | |
|--|-------------------------------|
| Information on toxicological effects: | No data available. |
| Skin effects: | No irritant effect. |
| Eye effects: | No irritating effect. |
| Sensitization: | No sensitizing effects known. |

12 Ecological information

| | |
|---------------------------------------|--|
| Aquatic toxicity: | Hazardous for water, do not empty into drains. |
| Persistence and degradability: | The product is degradable after prolonged exposure to natural weathering processes. |
| Other information: | This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents. |
| Bioaccumulative potential: | No further relevant information available. |
| Mobility in soil: | No further relevant information available. |
| Ecotoxicological effects: | |
| Remark: | Toxic for fish |
| Other adverse effects: | No further relevant information available. |

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

| | |
|--------------------------------------|--|
| UN-Number | UN1950 |
| DOT | N/A |
| DOT | Consumer Commodity ORM-D |
| ADR | Aerosols, flammable |
| Transport hazard class(es): | 1950 Aerosols, ENVIRONMENTALLY HAZARDOUS |
| Class | 2.1 |
| Marine pollutant: | Symbol (fish and tree) |
| Special precautions for user: | Warning: Gases |
| EMS Number: | F-D,S-U |
| Packaging Group: | -- |
| UN "Model Regulation": | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS |

(Contd. on page 4)

Safety Data Sheet

Printing date 01/10/2020

Revised On 01/06/2020

Trade name: ATHLETIC FIELD RED

(Contd. of page 3)

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

Toxic Substances Control Act**(TSCA):**

All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List**(DSL):**

All ingredients are listed or exempted.

Consumer Product Safety**Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

13463-67-7 titanium dioxide

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

142-82-5 heptane

D

1330-20-7 xylene (mix)

I

16 Other information**Contact:**

Regulatory Affairs