



TOOL CRIB SILICONE LUBE

#620-1500

A clear silicone lubricant for use on all sliding and rubbing surfaces. Authorized by USDA for use in Federally inspected meat and poultry plants. Comes with an extension tube for pinpoint application, and sprays in any position. Withstands high pressures, does not stain, and has low odor.

Suggested Uses:

Windows
Doors
Linkage
Speedometer cables
Shovels
Chutes

Packaging:

UPC Code	043281006695
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	13 ounces (369 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Cleanup	Lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	5%
VOC content	59%, can't exceed 60%
HAPs content	39%
Storage Temperature	40-90F
Application Temperature	40-100F
Lubricity Rating	Excellent
Appearance	Clear
Operating Speed	2000+ RPM
High Temperature Resistance	400F
Low Temperature Resistance	-40F
Heavy Load Capability	No
Shelf life	Guaranteed for 2 years
Food contact rating	H1 (incidental food contact)

12-11-2019