



TOOL CRIB TINTED IGNITION SEALER #620-1529 Red

Protect ignition systems from moisture, current leakage, acid, and corrosion. This coating is waterproof and flexible, and has an orange tint for uniform coverage. The dielectric strength is excellent and reduces electrical maintenance costs.

Suggested Uses:

Ignition systems.
Electrical equipment
Motor end windings
Communicator ends
Field coatings and armatures.

Packaging:

UPC Code	043281007146
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	14%
MIR value	0.86, cannot exceed 0.95
HAPs content	22%
Storage Temperature	40-100F
Application Temperature	50-90F
Gas Resistance	No
Heat Resistance	250F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To Touch 10 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: High Gloss, >85

*as measured on a 60 degree gloss meter

12-11-2019