

TOOL CRIB 5WAY CORROSION INHIBITOR & LUBE #620-1541



This is a specialized lightweight lubricant that both penetrates and protects against rust and corrosion. Displaces moisture, prevents flash rusting, and provides long term protection for metal. Does not contain silicone and meets following government specifications: MIL-C-16173D and MIL-C-23411 (metal corrosion test) and MIL-C-22235A (stain test).

Suggested Uses:

Lubricates hinges, threads, and pulleys
Loosen frozen nuts and bolts
Replacement for WD-40
Coat metal parts that sit outside to protect from corrosion

Packaging:

UPC Code	043281007078
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	14 ounces (397 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Lacquer thinner
Storage Temperature	40-100F
Application Temperature	50-90F
Flammability	Extremely Flammable
Specific Gravity	0.75
Solids Content	~20%
VOC content	Does not exceed 25%
HAPs Content	0%
Lubricity Rating	Excellent
Appearance	light amber
Weather Resistance	Excellent
Operating Speed	2000+ RPM
High Temperature Resistance	150F
Low Temperature Resistance -	20F
Heavy Load Capability	No
Shelf life Guaranteed for	2 years

1-2-2020