

REFLECTIVE COATINGS



A water-based reflective paint that provides a durable finish. The paint reflects back to the source of light. These coatings have excellent outdoor durability and can be used on a variety of surfaces to improve their visibility. For maximum reflectivity, apply two light coats over the Aluminum Base Coat (#16-532). DO NOT apply excessively thick coats as it will result in poor reflection and adhesion.

Suggested Uses:

Ramps
Steps
Door Frames
Trailers
Ladder Rungs
Railings

Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 12 square feet
Cleanup	Paint or lacquer thinner
Flammability	Flammable
Flash point	-42C
Specific Gravity	0.78
Solids Content	37%
MIR value	0.37, cannot exceed 0.95
HAPs content	0
Storage Temperature	40-100F
Application Temperature	50-90F
Gasoline Resistance	No
Heat Resistance	250F
Resin System	Waterborne
Shelf life Guaranteed for	1 year

Dry Time*:

To touch	10 minutes
To recoat	30 minutes
Traffic ready	overnight dry

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss: Flat, semi-rough texture

Available Colors:

<u>Part #</u>	<u>Description</u>	<u>UPC Code</u>
16-516	Yellow	043281001311
16-530	Fire Hydrant Red	043281001380

12-20-2019