

SEYMOUR ROOF PAINT



A professional grade roof paint that closely matches the original color of most roofing materials. Seamlessly blend the appearance of roofing accessories to asphalt shingles, terra cotta, and metal. Resists fading and protects against rust. Touch-up scratches & abrasions before or after installation. Not for anodized aluminum.

Suggested Uses:

Flashing
Vents
Skylights
Chimney caps
Satellite dishes
Window frames
Siding
Gutters

Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.78
Solids Content	20%
MIR value	0.77, cannot exceed 0.80
HAPs content	9%
Storage Temperature	40-90F
Application Temperature	50-100F
Abrasion Resistance	Good
Heat Resistance	250F
Resin System	V.T. Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	5 minutes
To topcoat	20 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <5

*as measured on a 60 degree gloss meter

Available Colors:

Part #	Description	UPC Code
16-1700	Weathered Wood	043281000628
16-1702	Hickory	043281000642
16-1703	Charcoal	043281000659

Available Colors:

Part #	Description	UPC Code
16-1704	Birchwood	043281000666
16-1705	Slate Gray	043281000673
16-1706	Flat Black	043281000680

12-20-2019