

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

## 1 Identification of the substance and manufacturer

**Trade name:** HI TECH BROWN

**Product code:** 0000160130

**Product category:** PC9a Paints and coatings.

**Manufacturer/Supplier:** Seymour of Sycamore  
917 Crosby Avenue  
Sycamore, IL 60178  
Phone: 815-895-9101 www.seymourpaint.com

**Emergency telephone number:** CHEMTEL 1-800-255-3924, 813-248-0585 \*if located outside the U.S.\*



## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word

Danger

### Hazard statements

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

### Precautionary statements

May cause damage to organs through prolonged or repeated exposure.

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

Do not breathe dust/fume/gas/mist/vapours/spray.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

Take off contaminated clothing and wash before reuse.

IF exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

67-64-1	Acetone	38.63%
74-98-6	propane	15.75%
108-88-3	Toluene	12.12%
106-97-8	n-butane	9.25%
108-10-1	methyl isobutyl ketone	2.1%
107-87-9	Methyl Propyl Ketone	1.86%
2807-30-9	Glycol Ether EP	1.58%

(Contd. on page 2)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

Trade name: HI TECH BROWN

108-65-6 PM acetate

(Contd. of page 1)

1.13%

## 4 First-aid measures

<b>After inhalation:</b>	Supply fresh air; consult doctor in case of complaints.
<b>After skin contact:</b>	Remove contaminated clothing. Wash exposed area with soap and water.
<b>After eye contact:</b>	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
<b>After swallowing:</b>	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
<b>Most important symptoms and effects:</b>	Dizziness
<b>Indication of any immediate medical attention needed:</b>	No further relevant information available.

## 5 Fire-fighting measures

<b>Extinguishing agents:</b>	CO <sub>2</sub> , extinguishing powder or water spray. Fight larger fires with water spray.
<b>Special hazards:</b>	Can form explosive gas-air mixtures.
<b>Protective equipment for firefighters:</b>	A respiratory protective device may be necessary.

## 6 Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures:</b>	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
<b>Methods and material for containment and cleaning up:</b>	Ensure adequate ventilation. Dispose contaminated material as waste according to section 13.

## 7 Handling and storage

<b>Precautions for safe handling</b>	Use only in well ventilated areas.
<b>Storage requirements:</b>	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

## 8 Exposure controls/personal protection

### Components with limit values that require monitoring at the workplace:

#### 67-64-1 Acetone

PEL (USA)	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m <sup>3</sup> , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m <sup>3</sup> , (500) NIC-250 ppm BEI

#### 74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV (USA)	refer to Appendix F

#### 108-88-3 Toluene

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

#### 106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm

#### 108-10-1 methyl isobutyl ketone

PEL (USA)	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV (USA)	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI

#### 107-87-9 Methyl Propyl Ketone

PEL (USA)	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
-----------	--

(Contd. on page 3)

US4

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

**Trade name: HI TECH BROWN**

(Contd. of page 2)

REL (USA)	Long-term value: 530 mg/m <sup>3</sup> , 150 ppm
TLV (USA)	Short-term value: 529 mg/m <sup>3</sup> , 150 ppm

**108-65-6 PM acetate**

WEEL (USA)	Long-term value: 50 ppm
------------	-------------------------

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

**108-88-3 Toluene**

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**108-10-1 methyl isobutyl ketone**

BEI (USA)	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----------	--

**Hygienic protection:** Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing.

Wash hands after use.  
Avoid contact with the eyes and skin.  
Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:** Protective gloves. The glove material must be impermeable and resistant to the substance.

**Eye protection:** Tightly sealed goggles

**9 Physical and chemical properties**

<b>Appearance:</b>	Aerosol.
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.
<b>pH-value:</b>	Not determined.
<b>Melting point/Melting range</b>	Undetermined.
<b>Boiling point:</b>	-44 °C (-47 °F)
<b>Flash point:</b>	-19 °C (-2 °F)
<b>Flammability (solid, gas):</b>	Extremely flammable.
<b>Decomposition temperature:</b>	Not determined.
<b>Auto igniting:</b>	Product is not self-igniting.
<b>Danger of explosion:</b>	In use, may form flammable/explosive vapour-air mixture.
<b>Lower Explosion Limit:</b>	1.7 Vol %
<b>Upper Explosion Limit:</b>	10.9 Vol %
<b>Vapor pressure:</b>	Not determined.
<b>Relative Density:</b>	Between 0.77 and 0.85 (Water equals 1.00)
<b>Vapour density</b>	Not determined.
<b>Evaporation rate</b>	Not applicable.
<b>Partition coefficient: n-octonal/water:</b>	Not determined.
<b>Solubility:</b>	Not determined.
<b>Viscosity:</b>	Not determined.
<b>VOC content:</b>	542.7 g/l / 4.53 lb/gl
<b>VOC content (less exempt solvents):</b>	45.1 %
<b>MIR Value:</b>	1.09
<b>Solids content:</b>	16.5 %

US4

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

Trade name: HI TECH BROWN

(Contd. of page 3)

## 10 Stability and reactivity

<b>Reactivity:</b>	Stable at normal temperatures.
<b>Conditions to avoid:</b>	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
<b>Chemical stability:</b>	Not fully evaluated.
<b>Possibility of hazardous reactions:</b>	No dangerous reactions known.
<b>Incompatible materials:</b>	No further relevant information available.
<b>Hazardous decomposition:</b>	No dangerous decomposition products known.

## 11 Toxicological information

### LD/LC50 values that are relevant for classification:

#### 106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

#### 108-10-1 methyl isobutyl ketone

Oral LD50 2100 mg/kg (rat)

Dermal LD50 16000 mg/kg (rab)

Inhalative LC50/4 h 8.3-16.6 mg/l (rat)

#### 108-65-6 PM acetate

Oral LD50 8500 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

**Information on toxicological effects:** No data available.**Sensitization:** No sensitizing effects known.

### Carcinogenic categories

#### IARC (International Agency for Research on Cancer)

108-88-3 Toluene

3

108-10-1 methyl isobutyl ketone

2B

#### NTP (National Toxicology Program)

None of the ingredients is listed.

#### OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

<b>Aquatic toxicity:</b>	Hazardous for water, do not empty into drains.
<b>Persistence and degradability:</b>	The product is degradable after prolonged exposure to natural weathering processes.
<b>Bioaccumulative potential:</b>	No further relevant information available.
<b>Mobility in soil:</b>	No further relevant information available.
<b>Other adverse effects:</b>	No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

<b>UN-Number</b>	UN1950
<b>DOT</b>	Aerosols, flammable
<b>ADR</b>	1950 Aerosols
<b>Transport hazard class(es):</b>	
<b>Class</b>	2.1
<b>Marine pollutant:</b>	No
<b>Special precautions for user:</b>	Warning: Gases
<b>EMS Number:</b>	F-D,S-U
<b>Packaging Group:</b>	--
<b>UN "Model Regulation":</b>	UN1950, Aerosols, 2.1

## 15 Regulatory information

### SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

### SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

108-10-1 methyl isobutyl ketone

**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

(Contd. on page 5)  
USA

# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

**Trade name: HI TECH BROWN**

(Contd. of page 4)

**California Proposition 65 chemicals known to cause cancer:**

108-10-1	methyl isobutyl ketone
13463-67-7	titanium dioxide
1333-86-4	Carbon black
100-41-4	ethyl benzene

**California Proposition 65 chemicals known to cause developmental toxicity:**

108-88-3 Toluene

**EPA:**

67-64-1	Acetone	I
108-88-3	Toluene	II
108-10-1	methyl isobutyl ketone	I

**16 Other information**
**Contact:** Regulatory Affairs

US4