

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

1 Identification of the substance and manufacturer

Trade name: BIG RIG ALUMINUM

Product code: 0000201611

Product category: PC9a Paints and coatings.

Manufacturer/Supplier: Seymour of Sycamore
917 Crosby Avenue
Sycamore, IL 60178
Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Water-react. 1 H260 In contact with water releases flammable gases which may ignite spontaneously.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Danger

Hazard statements

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
In contact with water releases flammable gases which may ignite spontaneously.
Causes skin irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.
Handle under inert gas. Protect from moisture.
Use personal protective equipment as required.
Do not breathe dust/fume/gas/mist/vapours/spray.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
If skin irritation occurs: Get medical advice/attention.
IF ON SKIN: Wash with plenty of water.
Take off contaminated clothing and wash before reuse.
IF exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
In case of fire: Use for extinction: CO₂, sand, extinguishing powder.
Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.
Specific treatment (see on this label).
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store in a dry place. Store in a closed container.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

108-88-3	Toluene	37.12%
74-98-6	propane	17.63%
106-97-8	n-butane	10.35%
67-64-1	Acetone	6.07%
64742-47-8	Mineral Spirits	6.01%
7429-90-5	Aluminum flake	2.99%
8052-41-3	Stoddard Solvent	1.61%

US4

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

Trade name: BIG RIG ALUMINUM

(Contd. of page 1)

4 First-aid measures

After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:	Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.
Most important symptoms and effects:	Dizziness
Indication of any immediate medical attention needed:	No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:	CO ₂ , extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards:	Can form explosive gas-air mixtures.
Protective equipment for firefighters:	A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and material for containment and cleaning up:	Ensure adequate ventilation. Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling	Use only in well ventilated areas.
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

108-88-3 Toluene

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm BEI

74-98-6 propane

PEL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (USA)	refer to Appendix F

106-97-8 n-butane

REL (USA)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (USA)	Short-term value: 2370 mg/m ³ , 1000 ppm

67-64-1 Acetone

PEL (USA)	Long-term value: 2400 mg/m ³ , 1000 ppm
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI

7429-90-5 Aluminum flake

PEL (USA)	Long-term value: 15*, 15** mg/m ³ *Total dust; ** Respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV (USA)	Long-term value: 1* mg/m ³ as Al; *as respirable fraction

(Contd. on page 3)

US4

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

Trade name: BIG RIG ALUMINUM

(Contd. of page 2)

8052-41-3 Stoddard Solvent

PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm

Ingredients with biological limit values:**108-88-3 Toluene**

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

67-64-1 Acetone

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with the skin. Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-110 °C (-166 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapour density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content:	591.9 g/l / 4.94 lb/gl
VOC content (less exempt solvents):	72.7 %
MIR Value:	1.81
Solids content:	22.8 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/26/2014

Revised On 09/26/2014

Trade name: BIG RIG ALUMINUM

(Contd. of page 3)

Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:**106-97-8 n-butane**

Inhalative | LC50/4 h | 658 mg/l (rat)

Information on toxicological effects: No data available.**Sensitization:** No sensitizing effects known.**Carcinogenic categories****IARC (International Agency for Research on Cancer)**

108-88-3 | Toluene

3

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Other adverse effects:	No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number	UN1950
DOT	Aerosols, flammable
ADR	1950 Aerosols
Transport hazard class(es):	
Class	2.1
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Packaging Group:	--
UN "Model Regulation":	UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 | Toluene

7429-90-5 | Aluminum flake

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

None of the ingredients in this product are listed.

California Proposition 65 chemicals known to cause developmental toxicity:

108-88-3 Toluene

EPA:

108-88-3 | Toluene

II

67-64-1 | Acetone

I

16 Other information

Contact: Regulatory Affairs