



BIG RIG RUST CONVERTER AND PRIMER #20-1600

Big Rig Rust Converter can be applied to any iron or steel surface to penetrate rust and chemically convert it into a protective black layer that will resist moisture and prevent future rust. Durable and tough, it can be left as is, but is also compatible with most top coats.

Suggested Uses:

Vehicles
Trailers
Fences
Railings
Sheet metal
Storage tanks

Packaging:

UPC Code	043281008891
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	16 ounces (454 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Lacquer thinner/paint thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	42%
MIR value	0.68, cannot exceed 0.70
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Excellent
Abrasion Resistance	Good
Gasoline Resistance	Yes
Heat Resistance	250F
Resin System	Alkyd
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	10 minutes
To recoat/topcoat	24 hours

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss meter

Additional Information:

For maximum protection, remove any as much loose rust as possible, then apply it like a primer to rusted surfaces.

12-20-2019