



INVERTED MIST ADHESIVE

#620-1512

This multi-purpose spray adhesive is ideal for bonding a wide variety of dissimilar materials. It is colorless and has a fast initial tack with low soak-in. Sprays upside down and cleans up easily with lacquer thinner.

Not compliant for sale in California.

Suggested Uses:

Cloth, cardboard, felt
 Hard rubber and plastic
 Fiberglass insulation panels, styrofoam
 Weather stripping and trim
 Wood, melamine, MDF
 Carpet and foam padding

Packaging:

UPC Code	043281009157
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	14 ounces (397 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Extremely Flammable"
Storage Temperature	30-100F
Application Temperature	40-90F
Specific Gravity	0.70
Solids Content	27%
VOC content	64%,
VOC compliancy:	Compliant for sale outside of CA – Does not exceed 65% VOC Not for Sale in CA – exceeds 30% VOC
HAPs Content	0
Heat Resistance	120F
Shear strength	51 psi
Shelf life	Guaranteed for 2 years
GreenGuard certified	No
LEED certified	No

Wait time before bonding 2 surfaces:

Approximately 3 minutes*

Permanent bond time:

Up to 15 minutes*

*Temperature and humidity may increase time needed for adhesive to become tacky.

Application method:

Evenly coat both surfaces to be joined, wait approximately 3 minutes until adhesive becomes tacky, then firmly press the two pieces together. Waiting too long may result in adhesive hardening and losing tackiness.

8-2-2019