



Acrylic Primer #16-531 Light Gray

This acrylic primer is all purpose and provides excellent adhesion to substrates such as hard plastic, metal, wood, fiberglass, and melamine. This product is flexible, sandable, fast drying, and provides a rust resistant base for any number of topcoats.

Suggested Uses:

Bumpers
Mailboxes
Automotive body panels
Lawn furniture

Packaging:

UPC Code	043281000079
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint thinner or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	16%
MIR value	0.68, cannot exceed 0.70
Storage Temperature	40-100F
Application Temperature	50-90F
Abrasion Resistance	Good
Heat Resistance	250F
Resin System	Acrylic
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch 10 minutes
To topcoat 30 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick
coats**

Gloss*: Flat, <15

*as measured on a 60 degree gloss
meter

Additional Information:

For maximum adhesion on plastic and melamine, sand lightly with fine sandpaper or steel wool prior to application.

12-20-2019