



MRO INDUSTRIAL PRIMERS

#620-1407 Red Oxide, #620-1431 Light Gray

A rust proof industrial primer formulated specifically for use with MRO Industrial Protective Coatings. This high solids paint gives twice the coverage of conventional aerosol primers. Heat resistant, VOC compliant, and fast drying.

Suggested Uses:

- Rusted metal
- Restore equipment
- Refinish machinery
- Protect metal structures

Packaging:

UPC Code 620-1407	043281006989
620-1431	043281006798
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	17 ounces (482 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4 F
Specific Gravity	0.81
Solids Content	24%
MIR value	0.69, cannot exceed 0.70
HAPs content	11%
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250F
Resin System	Phenolic
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch	5 minutes
To recoat	20 minutes

*At 72F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*:

Flat, <15
*as measured on a 60 degree gloss meter

12-20-2019