



## RAPID SEAL #20-146 Black

A durable black sealant that forms a protective skin that is both tough and flexible. Seals cracks, resists rust and corrosion, and blocks moisture. Can be used in a variety of applications---seal leaky gutters, rustproof the underbody of a car, prune a tree. Dries fast, does not sag, and can be topcoated.

### Suggested Uses:

Roof areas:  
Skylights  
Flashings  
Gutters  
Antenna installations  
Small cracks/holes in driveways  
Tree/Shrub pruning

### Packaging:

UPC Code	043281004671
Cans per case	12
Shipping weight per case	18 lbs.
Container	20 fluid ounce can
Label weight	18 ounces (511 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

### Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	60%
MIR value	0.86, cannot exceed 0.95
HAPs content	18%
Storage Temperature	40-90F
Application Temperature	50-100F
Heat Resistance	300F
Gasoline Resistance	No
Resin System	Petroleum Asphalt
Shelf life	Guaranteed for 2 years

### Dry Time\*:

To touch	10 minutes
To handle	4-6 hours

\*At 72F, 50% humidity,  
1.5 mil thickness

\*\*Curing/Recoat time is extended with  
multiple coats and excessively thick coats\*\*

**Gloss\*:** Low Lustre, 15-25

\*as measured on a 60 degree gloss meter