



TRUCK BED COATING

#20-41 Black

This product is a thick, durable black sealant that forms a protective skin that is both tough and flexible. Protects against corrosion and abrasion, withstands impacts, provides improved traction, and resists water. Truck Bed Liner greatly extends equipment and vehicle life expectancy.

Suggested Uses:

Truck beds
Trailers
Vehicle panels
Wheel wells
Repair existing liner coatings

Packaging:

UPC Code	043281008686
Cans per case	6
Shipping weight per case	18 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	21%
MIR value	0.86, cannot exceed 0.95
HAPs content	18%
Storage Temperature	40-90F
Application Temperature	50-100F
Durability	Very Good
Abrasion Resistance	Very Good
Heat Resistance	300F
Gasoline Resistance	No
Resin System	Polyurethane
Shelf life	Guaranteed for 2 years

Dry Time*:

To touch	30-45 minutes
To handle	8-10 hours
Return to service	24-36 hours
Full cure	~4 days

*At 72F, 50% humidity,
1.5 mil thickness

Curing/Recoat time is extended with multiple coats, cool temperatures, lack of air flow, and excessively thick coats

Gloss*: Low Lustre, 15-25

*dependant on temperature/humidity/air flow

12-19-2019