



BIG RIG PRIMERS

#20-1607 Red Oxide, #20-1631 Light Gray

A rust proof industrial primer formulated specifically for use with the Big Rig Coatings. This high solids paint gives twice the coverage of conventional aerosol primers. Heat resistant, VOC compliant, and fast drying.

Suggested Uses:

Rusted metal
Restore equipment
Refinish machinery
Protect metal structures

Packaging:

UPC Code 20-1607	043281009164
20-1631	043281006590
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	17 ounces (482 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4 F
Specific Gravity	0.81
Solids Content	24%
MIR value	0.69, cannot exceed 0.70
HAPs content	11%
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250F
Resin System	Phenolic
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch 5 minutes
To recoat 20 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*:

Flat, <15
*as measured on a 60 degree gloss meter

12-19-2019