



TOOL CRIB CONTRACTOR'S GRADE ADHESIVE

#620-1538

An all-purpose industrial adhesive for bonding substrate with differing textures. This colorless adhesive has fast tack properties, resists water, and is ideal for tacking on fiberglass insulation. Cleans up easily with lacquer thinner. Not recommended on vinyl plastic or vinyl coated cloth.

Not compliant for sale in California.

Suggested Uses:

Paper, cloth, cardboard, felt
 Rubber, fiberglass, styrofoam
 Certain types of plastic
 Weather stripping and trim
 Fiberglass insulation to heating ducts

Packaging:

UPC Code	043281003414
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	14 ounces (397 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Lacquer thinner
Storage Temperature	30-100F
Application Temperature	40-90F
Flammability	Extremely Flammable
Specific Gravity	0.75
Solids Content	21%
VOC content	53%
VOC compliancy:	Compliant for sale outside of CA – Does not exceed 65% VOC Not for Sale in CA – exceeds the 30% VOC limit
MIR Value	0.64
HAPs Content	0
Heat Resistance	200F
Shelf life	Guaranteed for 2 years
Food contact rating	No

8-1-2019